

Keysight Technologies

8163B Lightwave Multimeter

8164B Lightwave Measurement System

8166B Lightwave Multichannel System

Data Sheet



Keysight 8163B Mainframe

The Keysight Lightwave Multimeter system includes the mainframe and a variety of plug-in modules, suited for set-ups requiring:

- Single or dual channel power meters
- Single or dual wavelength fixed or tunable sources
- Loss test sets
- Return loss test sets

Specifications

Display	Graphical active color display 300 x 240 points visible, 4 updates per second
Display resolution (power meters)	0.0001 dB/dBm, 0.0 1pW to 10 pW (depending on power meter), up to 6.5 digits (user definable)
Chipset	Mobile Intel QM57Express
Compatibility	The Keysight 8163B mainframe supports all 8153A Series and 8163A & B Series modules. ¹
Trigger	True synchronous on all channels. Max. 100 kHz for triggering and 1 MHz (50% duty cycle) for external digital modulation.
Environmental	
Storage temperature	-40 °C to +70 °C
Operating temperature	0 °C to +45 °C
Humidity	< 95% rH from 0 °C to 55 °C The products are designed for pollution degree 2 The maximum operation altitude is 2000 m
Power	AC 100 to 240 V ± 10%, 50 to 60 Hz 5%, 120 VA max.
Dimensions (height x width x length)	88 mm x 213 mm x 380 mm (3.5" x 8.4" x 15")
Weight	net 4.200 kg (9.3 lbs), shipping 6.5 kg (14.5 lbs)
GPIB capability	All modes and parameters accessible via GP-IB interface
GPIB interface function codes ²	SH1, AH1, T6, L4, SR0, RL1, PP0, DC1, DT0, C0. SCPI Standard
GPIB interface performance	Max. 300 kB/sec (burst data rate during read of 12001 data points from power meter)
Parallel printer interface	Centronics
RS232 interface: max. baud rate	115200 bps
Number of modules	2 modules
Ordering information	
	Keysight 8163B Lightwave Multimeter
	Option 908 Rack mount kit
	08163-44101 Filler panel for empty slots

1. Keysight 8163B Series modules are NOT compatible with the HP 8153A Lightwave Multimeter.
2. For code compatibility to the HP 8153A Lightwave Multimeter please refer to the mainframe's Programming Guide, part number 08764-91026.

Keysight 8164B Mainframe

The Keysight 8164B mainframe, supports a range of high-performance tunable laser modules, as well as all of the fixed source and sensor modules of the 8153A and 8163A/B Lightwave Multimeter Series.

Specifications

Display	Graphical active color display, 640 x 480 points visible, 4 updates per second, VGA connector for external monitor
Display resolution	
Compatibility	The Keysight 8164B mainframe supports all 8153A Series and 8163A & B Series modules. ¹
Trigger	True synchronous on all channels. Max. 100 kHz for triggering and 1 MHz (50% duty cycle) for external digital modulation.
Environmental	
Storage temperature	-40 °C to +70 °C
Operating temperature	0 °C to +35 °C
Humidity	< 80% rH from 10 °C to 35 °C The products are designed for pollution degree 2 The maximum operation altitude is 2000 m
Power	AC 100 to 240 V ± 10%, 50/60 Hz , 280 VA max.
Dimensions (height x width x length)	145 mm x 426 mm x 545 mm (5.8" x 16.9" x 21.6")
Weight	net 20 kg, shipping 23 kg
GPIB capability	All modes and parameters accessible via GP-IB interface
GPIB interface function codes ²	SH1, AH1, T6, L4, SR0, RL1, PP0, DC1, DT0, C0. SCPI Standard
GPIB interface performance	Max. 300 kB/sec (burst data rate during read of 12001 data points from power meter)
Parallel printer interface	Centronics
RS232 interface: max. baud rate	115200 bps
Number of modules	4/1 modules
Ordering information	
Keysight 8164B Lightwave Multimeter	
Option 908 Rack mount kit	
08163-44101 Filler panel for empty slots (compact slots only)	

1. Keysight 8163B Series modules are NOT compatible with the HP 8153A Lightwave Multimeter.
2. For code compatibility to the HP 8153A Lightwave Multimeter please refer to the mainframe's Programming Guide, part number 08764-91026.

Keysight 8166B Mainframe

The Keysight 8166B mainframe can be easily integrated into test environments by using plug and play drivers over GPIB, or by using the configurable hardware input and output trigger ports.

All modules of the 8163A/B Lightwave Multimeter family can be used in any combination in the Multichannel System.

Specifications

Display	Graphical active color display, 300 x 240 points visible, 4 updates per second, VGA connector for external monitor
Display resolution	0.0001 dB/dBm, 0.01 pW to 10 pW (depending on power range), up to 6.5 digits (user definable)
Compatibility	The Keysight 8166B mainframe supports all modules from the 8163A/B Lightwave Multimeter series. ¹
Trigger	True synchronous on all channels. Max. 100 kHz for triggering and 1 MHz (50% duty cycle) for external digital modulation.
Environmental	
Storage temperature	-40 °C to +70 °C
Operating temperature	0 °C to +45 °C
Humidity	< 95% rH from 0 °C to 45 °C
	The products are designed for pollution degree 2
	The maximum operation altitude is 2000 m
Power	AC 100 to 240 V ± 10%, 50/60 Hz, 450 VA max.
Dimensions (height x width x length)	240 mm x 430 mm x 580 mm (9.5" x 17" x 23")
Weight	net 23 kg, shipping 45 kg
GPIB capability	All modes and parameters accessible via GP-IB interface
GPIB interface function codes ²	SH1, AH1, T6, L4, SR0, RL1, PP0, DC1, DT0, C0. SCPI Standard
GPIB interface performance	Max. 300 kB/sec (burst data rate during read of 12001 data points from power meter)
Parallel printer Interface	Centronics
RS232 interface: max. baud rate	115200 bps
Number of modules	17 modules
Ordering information	
Keysight 8166B Lightwave Multimeter	
Option 908 Rack mount kit	
08163-44101 Filler panel for empty slots	

1. Modules designed for the HP 8153A Lightwave Multimeter are NOT compatible with the Keysight 8166A/B Lightwave Multichannel System.
2. For code compatibility to the HP 8153A Lightwave Multimeter please refer to the mainframe's Programming Guide, part number 08764-91026.

myKeysight

myKeysight

www.keysight.com/find/mykeysight

A personalized view into the information most relevant to you.



www.axiestandard.org

AdvancedTCA® Extensions for Instrumentation and Test (AXIe) is an open standard that extends the AdvancedTCA for general purpose and semiconductor test. Keysight is a founding member of the AXIe consortium. ATCA®, AdvancedTCA®, and the ATCA logo are registered US trademarks of the PCI Industrial Computer Manufacturers Group.



www.lxistandard.org

LAN eXtensions for Instruments puts the power of Ethernet and the Web inside your test systems. Keysight is a founding member of the LXI consortium.



www.pxisa.org

PCI eXtensions for Instrumentation (PXI) modular instrumentation delivers a rugged, PC-based high-performance measurement and automation system.



Three-Year Warranty

www.keysight.com/find/ThreeYearWarranty

Keysight's commitment to superior product quality and lower total cost of ownership. The only test and measurement company with three-year warranty standard on all instruments, worldwide.



Keysight Assurance Plans

www.keysight.com/find/AssurancePlans

Up to five years of protection and no budgetary surprises to ensure your instruments are operating to specification so you can rely on accurate measurements.



www.keysight.com/quality

Keysight Technologies, Inc.
DEKRA Certified ISO 9001:2008
Quality Management System

Keysight Channel Partners

www.keysight.com/find/channelpartners

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

www.keysight.com/find/lightwave

www.keysight.com/find/oct

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

Americas

Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

Europe & Middle East

Austria	0800 001122
Belgium	0800 58580
Finland	0800 523252
France	0805 980333
Germany	0800 6270999
Ireland	1800 832700
Israel	1 809 343051
Italy	800 599100
Luxembourg	+32 800 58580
Netherlands	0800 0233200
Russia	8800 5009286
Spain	0800 000154
Sweden	0200 882255
Switzerland	0800 805353
	Opt. 1 (DE)
	Opt. 2 (FR)
	Opt. 3 (IT)
United Kingdom	0800 0260637

For other unlisted countries:
www.keysight.com/find/contactus
(BP-07-10-14)

